



Throughbolt anchor - zinc plated - seismic - Option 1

Reference: BZ-S



Dessin technique

Description longue (Informations techniques)

Diameter: M8

Diameter: M12

Diameter: M10

Family: Heavy duty anchors

Assessment: Fire120

Assessment: Seismic assessment C2

Assessment: ETA opt. 1

Assessment: ETA

Base material: Cracked concrete

Material: Zinc plated steel

Type: Throughbolt

Loads: Heavy

Loads: Medium

Screw head: Threaded

Tableau des caracteristiques

Diamètre	Longueur	tfix	ØDrill	h1	SW	tinst	Référence
M8	68	4	8	70	13	20	BZ-S-08X068
M8	75	10	8	70	13	20	BZ-S-08X075
M8	90	25	8	70	13	20	BZ-S-08X090
M8	115	50	8	70	13	20	BZ-S-08X115
M10	90	10	10	80	17	40	BZ-S-10X090
M10	105	25	10	80	17	40	BZ-S-10X105
M10	115	35	10	80	17	40	BZ-S-10X115
M10	135	55	10	80	17	40	BZ-S-10X135
M12	110	10	12	100	19	60	BZ-S-12X110
M12	120	20	12	100	19	60	BZ-S-12X120
M12	145	45	12	100	19	60	BZ-S-12X145
M16	130	10	16	115	24	120	BZ-S-16X130
M16	150	30	16	115	24	120	BZ-S-16X150
M16	185	60	16	115	24	120	BZ-S-16X185