



Heavy duty anchor - Countersunk head screw

Reference: HVE03



Dessin technique

Description longue (Informations techniques)

Family: Heavy duty anchors
Assessment: ETA opt. 1
Assessment: Fire120
Assessment: Seismic assessment C1
Assessment: ETA
Base material: Cracked concrete
Material: Zinc plated steel
Type: Plug
Loads: Heavy
Loads: Medium
Screw head: Countersunk

Tableau des caracteristiques

Diamètre	Longueur	ØDrill	h1	tfix	tinst	Hef	Socket	Référence
M6	85	10	80	20	15	55	HEX 4	HVE03-10/20
M6	105	10	80	40	15	55	HEX 4	HVE03-10/40
M6	125	10	80	60	15	55	HEX 4	HVE03-10/60
M8	85	12	90	15	30	60	HEX 5	HVE03-12/15
M8	105	12	90	35	30	60	HEX 5	HVE03-12/35
M8	125	12	90	55	30	60	HEX 5	HVE03-12/55
M10	110	16	100	30	50	70	HEX 6	HVE03-16/30
M10	130	16	100	50	50	70	HEX 6	HVE03-16/50
M12	120	18	120	20	100	90	HEX 8	HVE03-18/20
M12	140	18	120	40	100	90	HEX 8	HVE03-18/40