



standard blind rivet - alu/steel - countersunk head 120°

Reference: ASK



Dessin technique

Description longue (Informations techniques)

Diameter: 3,0

Diameter: 4,0

Diameter: 2,4

Diameter: 3,2

Diameter: 4,8

Type: Standard

Body / mandrel material: Aluminium/Steel

Head: Countersunk

MAXIMUM CLAMP (mm): 1,5

maximum assembly range (mm): 30,0

Maximum tensile: 353

Maximum Shear : 314

Tableau des caracteristiques

Diamètre	Longueur	Shear	ØDrill	Tensile	G	K	Référence
2,4	10,0	314	2.5	353	6.0-8.0	5.0	ASK2410
3,0	6,0	620	3.1	810	1.5-3.5	6.0	ASK3006
3,0	8,0	620	3.1	810	3.5-5.5	6.0	ASK3008
3,0	10,0	620	3.1	810	5.5-7.0	6.0	ASK3010
3,0	12,0	620	3.1	810	7.0-9.0	6.0	ASK3012
3,2	6,0	3.3	760	980	1.5-3.5	6.0	ASK3206
3,2	8,0	3.3	760	980	3.5-5.0	6.0	ASK3208
3,2	10,0	3.3	760	980	5.0-7.0	6.0	ASK3210
3,2	12,0	3.3	760	980	7.0-9.0	6.0	ASK3212
3,2	14,0	3.3	760	980	9.0-10.5	6.0	ASK3214
3,2	16,0	3.3	760	980	10.5-13.0	6.0	ASK3216
4,0	6,0	4.1	1?080	1?580	1.5-3.0	7.5	ASK4006
4,0	8,0	4.1	1?080	1?580	3.0-5.0	7.5	ASK4008
4,0	10,0	4.1	1?080	1?580	5.0-6.5	7.5	ASK4010
4,0	12,0	4.1	1?080	1?580	6.5-8.5	7.5	ASK4012
4,0	16,0	4.1	1?080	1?580	10.5-12.5	7.5	ASK4016
4,0	18,0	4.1	1?080	1?580	12.5-14.5	7.5	ASK4018
4,0	20,0	1?080	4.1	1?580	14.5-16.5	7.5	ASK4020
4,8	8,0	1?580	4.9	2?230	2.0-4.5	9.0	ASK4808
4,8	10,0	1?580	4.9	2?230	4.5-6.0	9.0	ASK4810
4,8	12,0	1?580	4.9	2?230	6.0-8.0	9.0	ASK4812
4,8	14,0	1?580	4.9	2?230	8.0-10.0	9.0	ASK4814
4,8	16,0	1?580	4.9	2?230	10.0-12.0	9.0	ASK4816
4,8	18,0	1?580	4.9	2?230	12.0-14.0	9.0	ASK4818
4,8	20,0	1?580	4.9	2?230	14.0-16.0	9.0	ASK4820
4,8	25,0	1?580	4.9	2?230	16.0-21.0	9.0	ASK4825
4,8	30,0	1?580	4.9	2?230	21.0-25.0	9.0	ASK4830
4,8	35,0	1?580	4.9	2?230	25.0-30.0	9.0	ASK4835
2,4	6,0						ASK2406