



standard blind rivet - stainless steel A2/stainless steel A2 - dome head

Reference: BTB



Dessin technique

Description longue (Informations techniques)

Diameter: 4,0

Diameter: 2,4

Diameter: 6,4

Diameter: 3,2

Diameter: 4,8

Diameter: 3,0

Type: Standard

Body / mandrel material: Stainless steel A2 / Stainless steel A2

Head: Dome head

MAXIMUM CLAMP (mm): 1,0

maximum assembly range (mm): 25,0

Maximum tensile: 1500

Maximum Shear : 1100

Tableau des caracteristiques

Diamètre	Longueur	G	K	Shear	ØDrill	Tensile	Référence
2.4	6.0	1.0-3.0	5.0	1100	Ø2.5	1500	BTD2406
3.0	6.0	1.0-3.0	6.5	1800	Ø3.1	2200	BTD3006
3.0	8.0	3.0-5.0	6.5	1800	Ø3.1	2200	BTD3008
3.0	10.0	5.0-7.0	6.5	1800	Ø3.1	2200	BTD3010
3.0	12.0	7.0-9.0	6.5	1800	Ø3.1	2200	BTD3012
3.2	6.0	1.0-3.0	6.5	1900	Ø3.3	2500	BTD3206
3.2	8.0	3.0-5.0	1900	6.5	Ø3.3	2500	BTD3208
3.2	10.0	5.0-7.0	6.5	1900	Ø3.3	2500	BTD3210
3.2	12.0	7.0-9.0	6.5	1900	Ø3.3	2500	BTD3212
3.2	14.0	9.0-12.0	6.5	1900	Ø3.3	2500	BTD3215
4.0	6.0	1.0-2.5	8.0	2700	Ø4.1	3500	BTD4006
4.0	8.0	2.5-4.5	8.0	2700	Ø4.1	3500	BTD4008
4.0	10.0	4.5-6.5	8.0	2700	Ø4.1	3500	BTD4010
4.0	12.0	6.5-9.5	8.0	2700	Ø4.1	3500	BTD4012
4.0	16.0	9.5-12.0	8.0	2700	Ø4.1	3500	BTD4016
4.0	18.0	12.0-14.0	8.0	2700	Ø4.1	3500	BTD4018
4.0	20.0	14.0-16.0	8.0	2700	Ø4.1	3500	BTD4020
4.8	8.0	1.5-4.0	9.0	4000	Ø4.9	5000	BTD4808
4.8	10.0	4.0-6.0	9.0	4000	Ø4.9	5000	BTD4810
4.8	12.0	6.0-8.0	9.0	4000	Ø4.9	5000	BTD4812
4.8	14.0	8.0-9.5	9.0	4000	Ø4.9	5000	BTD4814
4.8	16.0	9.5-11.0	9.0	4000	Ø4.9	5000	BTD4816
4.8	18.0	11.0-13.0	9.0	4000	Ø4.9	5000	BTD4818
4.8	20.0	13.0-15.0	9.0	4000	Ø4.9	5000	BTD4820
4.8	25.0	17.0-20.0	9.0	4000	Ø4.9	5000	BTD4825
4.8	30.0	21.0-25.0	9.0	4000	Ø4.9	5000	BTD4830
6.4	12.0	4.0-6.0	12.0	6500	Ø6.5	8850	BTD6412
6.4	15.0	6.0-9.0	12.0	6500	Ø6.5	8850	BTD6415
6.4	18.0	9.0-13.0	12.0	6500	Ø6.5	8850	BTD6418
6.4	20.0	13.0-16.0	12.0	6500	Ø6.5	8850	BTD6420
6.4	25.0	16.0-20.0	12.0	6500	Ø6.5	8850	BTD6425