



TFAC 120° countersunk head, bright zinc-plated steel

Reference: TFAC



Dessin technique

Description longue (Informations techniques)

Diameter: 4,2-4,5

Diameter: 4,8-5,0

Diameter: 6,3-6,0

Diameter: 5,5

Family: Vis bois

Material: white zinc plated steel

Head: Countersunk

MAXIMUM ASSEMBLY CAPACITY (mm): 70

MINIMUM DRILL CAPACITY FOR STEEL (mm): 3

Socket type: PHILLIPS (PH-PZ)

MAXIMUM DRILL CAPACITY FOR STEEL (mm): 6

MINIMUM ASSEMBLY CAPACITY(mm): 12

Tableau des caracteristiques

Diamètre	Longueur	G	Shear	Tensile	Drill capacity for steel	wrench	maximum speed	Socket	Référence
4.2	32	19	4360	7000	3.0	4800		PH2	TFAC42032
4.2	38	25	4360	7000	3.0	4800		PH2	TFAC42038
4.8	38	23	6280	10000	4.0	7000	2000	PH2	TFAC48038
4.8	45	32	6280	10000	4.0	7000	2000	PH2	TFAC48045
4.8	50	35	6280	10000	4.0	7000	2000	PH2	TFAC48050
4.8	75	60	6280	10000	4.0	7000	2000	PH2	TFAC48075
5.5	38	23	8360	12500	5.0	10500	1750	PH3	TFAC55038
5.5	50	35	8360	12500	5.0	10500	1750	PH3	TFAC55050
5.5	60	45	8360	12500	5.0	10500	1750	PH3	TFAC55060
5.5	65	50	8360	12500	5.0	10500	1750	PH3	TFAC55065
5.5	85	70	8360	12500	5.0	10500	1750	PH3	TFAC55085
6.3	50	34	12270	17000	6.0	17000	1500	PH3	TFAC63050
6.3	70	54	12270	17000	6.0	17000	1500	PH3	TFAC63070