



Concrete screw - zinc plated - Countersunk head

Reference: BTF



Dessin technique

Description longue (Informations techniques)

Family: Heavy duty anchors

K:

Use: Indoor/Outdoor

Assessment: ETA opt. 1

Assessment: ETA

Assessment: Fire120

Assessment: Seismic assessment C2

Base material: Cracked concrete

Material: Zinc plated steel

Type: Screws

Loads: Heavy

Loads: Medium

Screw head: Hex

Socket:

Tableau des caracteristiques

Diamètre	Longueur	K	ØDrill	h1	tfix	tinst	ho	Hef	Socket	Référence
6	70	16	6	75	10	20	6	60	T30	BTF06070
6	100	16	6	75	40	20	6	60	T30	BTF06100
6	140	16	6	75	80	20	6	60	T30	BTF06140
8	80	20	8	85	10	50	7	70	TX40	BTF08080
8	100	20	8	85	30	50	7	70	TX40	BTF08100
8	160	20	8	85	90	50	7	70	TX40	BTF08160
10	100	24	10	100	20	80	8,5	80	TX50	BTF10100
10	120	24	10	100	40	80	8,5	80	TX50	BTF10120
10	180	24	10	100	100	80	8,5	80	TX50	BTF10180