



Throughbolt anchor - zinc plated - seismic - Option 1

Reference: BZ-S



Dessin technique

Description longue (Informations techniques)

Diameter: M10
Diameter: M8
Diameter: M12
Family: Heavy duty anchors
Assessment: Fire120
Assessment: Seismic assessment C2
Assessment: ETA opt. 1
Assessment: ETA
Base material: Cracked concrete
Material: Zinc plated steel
Type: Throughbolt
Loads: Heavy
Loads: Medium
Screw head: Threaded

Tableau des caracteristiques

Diamètre	Longueur	ØDrill	h1	tfix	SW	tinst	Référence
M8	68	8	70	4	13	20	BZ-S-08X068
M8	75	8	70	10	13	20	BZ-S-08X075
M8	90	8	70	25	13	20	BZ-S-08X090
M8	115	8	70	50	13	20	BZ-S-08X115
M10	90	10	80	10	17	40	BZ-S-10X090
M10	105	10	80	25	17	40	BZ-S-10X105
M10	115	10	80	17	35	40	BZ-S-10X115
M10	135	10	80	55	17	40	BZ-S-10X135
M12	110	12	100	10	19	60	BZ-S-12X110
M12	120	12	100	20	19	60	BZ-S-12X120
M12	145	12	100	45	19	60	BZ-S-12X145
M16	130	16	115	10	24	120	BZ-S-16X130
M16	150	16	115	24	30	120	BZ-S-16X150
M16	185	16	115	60	24	120	BZ-S-16X185