



# standard blind rivet - alu/steel - dome head - RAL9005

Reference: ABD



## Dessin technique

### Description longue (Informations techniques)

Diameter: 4,8

Diameter: 4,0

Diameter: 3,2

Type: Standard

Socket:

Body / mandrel material: Aluminium/Steel

Colour: Black RAL9005

Head: Dome head

MAXIMUM CLAMP (mm): 1,5

maximum assembly range (mm): 21,0

Maximum tensile: 980

Maximum Shear : 760

# Tableau des caracteristiques

| Diamètre | Longueur | G         | Shear | K     | ØDrill | Tensile | Référence |
|----------|----------|-----------|-------|-------|--------|---------|-----------|
| 3,2      | 6,0      | 1.5-3.5   | 760   | 6.5   | 3.3    | 980     | ABD3206   |
| 3,2      | 8,0      | 3.5-5.0   | 760   | 6.5   | 3.3    | 980     | ABD3208   |
| 3,2      | 10,0     | 5.0-7.0   | 760   | 6.5   | 3.3    | 980     | ABD3210   |
| 3,2      | 12,0     | 7.0-9.0   | 760   | 6.5   | 3.3    | 980     | ABD3212   |
| 3,2      | 14,0     | 9.0-11.0  | 760   | 6.5   | 3.3    | 980     | ABD3214   |
| 4,0      | 8,0      | 3.0-5.0   | 17080 | 8.0   | 4.1    | 17580   | ABD4008   |
| 4,0      | 10,0     | 5.0-6.5   | 17080 | 8.0   | 4.1    | 17580   | ABD4010   |
| 4,0      | 12,0     | 6.5-8.5   | 17080 | 8.0   | 4.1    | 17580   | ABD4012   |
| 4,0      | 16,0     | 10.5-12.5 | 17080 | 8.0   | 4.1    | 17580   | ABD4016   |
| 4,0      | 18,0     | 12.5-14.5 | 8.0   | 17080 | 4.1    | 17580   | ABD4018   |
| 4,0      | 20,0     | 14.5-16.5 | 8.0   | 17080 | 4.1    | 17580   | ABD4020   |
| 4,8      | 10,0     | 4.5-6.0   | 9.5   | 17580 | 4.8    | 27230   | ABD4810   |
| 4,8      | 12,0     | 6.0-8.0   | 9.5   | 17580 | 4.8    | 27230   | ABD4812   |
| 4,8      | 16,0     | 10.0-12.0 | 9.5   | 17580 | 4.8    | 27230   | ABD4816   |
| 4,8      | 20,0     | 14.0-16.0 | 9.5   | 17580 | 4.8    | 27230   | ABD4820   |
| 4,8      | 25,0     | 18.0-21.0 | 9.5   | 17580 | 4.8    | 27230   | ABD4824   |