



standard blind rivet - alu/steel - countersunk head 120°

Reference: ASK



Dessin technique

Description longue (Informations techniques)

Diameter: 4,0

Diameter: 2,4

Diameter: 3,2

Diameter: 4,8

Diameter: 3,0

Type: Standard

Body / mandrel material: Aluminium/Steel

Head: Countersunk

MAXIMUM CLAMP (mm): 1,5

maximum assembly range (mm): 30,0

Maximum tensile: 353

Maximum Shear : 314

Tableau des caracteristiques

Diamètre	Longueur	G	Shear	K	ØDrill	Tensile	Référence
2,4	10,0	6.0-8.0	314	5.0	2.5	353	ASK2410
3,0	6,0	1.5-3.5	620	6.0	3.1	810	ASK3006
3,0	8,0	3.5-5.5	620	6.0	3.1	810	ASK3008
3,0	10,0	5.5-7.0	620	6.0	3.1	810	ASK3010
3,0	12,0	7.0-9.0	620	6.0	3.1	810	ASK3012
3,2	6,0	1.5-3.5	760	6.0	3.3	980	ASK3206
3,2	8,0	3.5-5.0	760	6.0	3.3	980	ASK3208
3,2	10,0	5.0-7.0	760	6.0	3.3	980	ASK3210
3,2	12,0	7.0-9.0	760	6.0	3.3	980	ASK3212
3,2	14,0	9.0-10.5	760	6.0	3.3	980	ASK3214
3,2	16,0	10.5-13.0	760	6.0	3.3	980	ASK3216
4,0	6,0	1.5-3.0	17080	7.5	4.1	17580	ASK4006
4,0	8,0	3.0-5.0	17080	7.5	4.1	17580	ASK4008
4,0	10,0	5.0-6.5	7.5	17080	4.1	17580	ASK4010
4,0	12,0	6.5-8.5	7.5	17080	4.1	17580	ASK4012
4,0	16,0	10.5-12.5	7.5	17080	4.1	17580	ASK4016
4,0	18,0	12.5-14.5	7.5	17080	4.1	17580	ASK4018
4,0	20,0	14.5-16.5	17080	7.5	4.1	17580	ASK4020
4,8	8,0	2.0-4.5	17580	9.0	4.9	27230	ASK4808
4,8	10,0	4.5-6.0	17580	9.0	4.9	27230	ASK4810
4,8	12,0	6.0-8.0	17580	9.0	4.9	27230	ASK4812
4,8	14,0	8.0-10.0	17580	9.0	4.9	27230	ASK4814
4,8	16,0	10.0-12.0	17580	9.0	4.9	27230	ASK4816
4,8	18,0	12.0-14.0	17580	9.0	4.9	27230	ASK4818
4,8	20,0	14.0-16.0	17580	9.0	4.9	27230	ASK4820
4,8	25,0	16.0-21.0	17580	9.0	4.9	27230	ASK4825
4,8	30,0	21.0-25.0	17580	9.0	4.9	27230	ASK4830
4,8	35,0	25.0-30.0	17580	9.0	4.9	27230	ASK4835
2,4	6,0						ASK2406