



standard blind rivet - alu/alu - dome head

Reference: HD



Dessin technique

Description longue (Informations techniques)

Diameter: 4,0

Diameter: 3,2

Diameter: 4,8

Type: Standard

Socket:

Body / mandrel material: Aluminium-Aluminium

Head: Dome head

MAXIMUM CLAMP (mm): 1,5

maximum assembly range (mm): 25,0

Maximum tensile: 667

Maximum Shear : 534

Tableau des caracteristiques

Diamètre	Longueur	G	Shear	K	ØDrill	Tensile	Référence
3,2	6,0	1.5-3.5	534	6.5	3.3	667	HD3206
3,2	8,0	3.5-5.0	534	6.5	3.3	667	HD3208

3,2	10,0	5.0-7.0	534	6.5	3.3	667	HD3210
3,2	12,0	7.0-8.5	534	6.5	3.3	667	HD3212
3,2	16,0	10.5-13.0	534	6.5	3.3	667	HD3216
4,0	6,0	1.5-3.5	845	8.0	4.1	1?022	HD4006
4,0	8,0	3.5-5.0	845	8.0	4.1	1?022	HD4008
4,0	10,0	5.0-6.5	845	8.0	4.1	1?022	HD4010
4,0	12,0	6.5-8.5	845	8.0	4.1	1?022	HD4012
4,0	14,0	8.5-10.5	845	8.0	4.1	1?022	HD4014
4,0	16,0	10.5-12.5	845	8.0	4.1	1?022	HD4016
4,0	18,0	12.5-14.5	845	8.0	4.1	1?022	HD4018
4,0	20,0	14.5-16.5	845	8.0	4.1	1?022	HD4020
4,8	8,0	3.0-4.5	1?155	9.5	4.9	1?422	HD4808
4,8	10,0	4.5-6.0	1?155	9.5	4.9	1?422	HD4810
4,8	12,0	6.0-7.5	1?155	9.5	4.9	1?422	HD4812
4,8	14,0	7.5-9.0	1?155	9.5	4.9	1?422	HD4814
4,8	16,0	9.0-11.5	9.5	1?155	4.9	1?422	HD4816
4,8	18,0	11.5-13.0	9.5	1?155	4.9	1?422	HD4818
4,8	20,0	13.0-15.0	9.5	1?155	4.9	1?422	HD4820
4,8	25,0	15.0-20.0	9.5	1?155	4.9	1?422	HD4825
4,8	30,0	20.0-25.0	9.5	1?155	4.9	1?422	HD4830