



multigrip blind rivet - alu/steel - dome head

Reference: UD



Dessin technique

Description longue (Informations techniques)

Diameter: 4,0

Diameter: 3,2

Diameter: 4,8

Type: Multigrip

Socket:

Body / mandrel material: Aluminium/Steel

Head: Dome head

MAXIMUM CLAMP (mm): 1,0

maximum assembly range (mm): 24,0

Maximum tensile: 980

Maximum Shear : 680

Tableau des caracteristiques

Diamètre	Longueur	G	Shear	K	ØDrill	Tensile	Référence
3,2	6,0	1.0-4.0	680	6.0	3.3	980	UD3206
3,2	8,0	1.0-5.0	680	6.0	3.3	980	UD3208
3,2	9,5	2.5-7.0	680	6.0	3.3	980	UD3210
3,2	12,7	4.5-9.0	680	6.0	3.3	980	UD3212
4,0	6,0	1.0-3.5	17150	6.0	4.1	17600	UD4006
4,0	9,5	1.5-6.5	17150	6.0	4.1	17600	UD4010
4,0	12,7	4.5-9.0	17150	6.0	4.1	17600	UD4012
4,0	17,0	8.5-13.0	6.0	17150	4.1	17600	UD4016
4,8	10,3	1.0-6.0	9.5	17500	4.9	27350	UD4810
4,8	12,0	2.0-8.0	9.5	17500	4.9	27350	UD4812
4,8	15,1	5.0-10.5	9.5	17500	4.9	27350	UD4815
4,8	17,0	7.0-12.0	9.5	17500	4.9	27350	UD4816
4,8	20,0	10.0-16.0	9.5	17500	4.9	27350	UD4820
4,8	24,8	12.5-20.0	9.5	17500	4.9	27350	UD4825
4,8	30,0	16.5-24.0	9.5	17500	4.9	27350	UD4830