



sealed blind rivet alu/steel - dome head

Reference: WAD



Dessin technique

Description longue (Informations techniques)

Diameter: 3,2

Diameter: 4,8

Diameter: 4,0

Diameter: 6,4

K:

Type: Sealed

Socket:

Body / mandrel material: Aluminium/Steel

Head: Dome head

MAXIMUM CLAMP (mm): 0,5

maximum assembly range (mm): 20,0

Maximum tensile: 1245

Maximum Shear : 1070

Tableau des caracteristiques

Diamètre	Longueur	G	K	Shear	ØDrill	Tensile	Référence
3,2	6,5	0.5-2.0	6.0	1070	3.3	1245	WAD3206
3,2	8,0	2.0-3.5	6.0	1070	3.3	1245	WAD3208
3,2	9,5	3.5-5.0	1070	6.0	3.3	1245	WAD3210
3,2	12,7	6.5-8.0	1070	6.0	3.3	1245	WAD3212
4,0	8,0	0.5-3.5	1710	8.0	4.1	2240	WAD4008
4,0	9,5	3.5-4.5	1710	8.0	4.1	2240	WAD4010
4,0	12,7	6.5-8.0	1710	8.0	4.1	2240	WAD4012
4,0	15,0	8.0-10.5	1710	8.0	4.1	2240	WAD4015
4,8	8,0	1.0-3.0	2230	9.5	4.9	3070	WAD4808
4,8	9,0	2.5-4.0	2230	9.5	4.9	3070	WAD4809
4,8	9,5	3.0-4.5	2230	9.5	4.9	3070	WAD4810
4,8	12,5	6.0-7.5	2230	9.5	4.9	3070	WAD4812
4,8	14,0	7.5-9.0	2230	9.5	4.9	3070	WAD4814
4,8	16,0	9.0-11.0	2230	9.5	4.9	3070	WAD4816
4,8	18,0	11.0-13.0	2230	9.5	4.9	3070	WAD4818
4,8	21,0	13.0-16.0	2230	9.5	4.9	3070	WAD4821
4,8	25,0	16.0-20.0	2230	9.5	4.9	3070	WAD4825
6,4	12,5	1.5-6.0	3950	12.7	6.5	5000	WAD6412
6,4	16,0	6.0-8.0	3950	12.7	6.5	5000	WAD6416