



structural rivet hyperiv - stainless steel A2/stainless steel A2 - dome head

Reference: HPTD



Dessin technique

Description longue (Informations techniques)

Diameter: 3,2

Diameter: 4,8

Diameter: 4,0

Diameter: 6,4

Type: structural standard

Body / mandrel material: Stainless steel A2 / Stainless steel A2

Head: Dome head

MAXIMUM CLAMP (mm): 1,0

maximum assembly range (mm): 14,5

Maximum tensile: 1600

Maximum Shear : 1600

Tableau des caracteristiques

Diamètre	Longueur	G	K	Shear	ØDrill	Tensile	Référence
3.2	7.0	1.0-3.0	6.0	1600	3.4	1600	HPTD32070
3.2	9.0	3.0-5.0	6.0	1600	3.4	1600	HPTD32090
3.2	11.0	5.0-7.0	6.0	1600	3.4	1600	HPTD32110
4.0	8.0	1.0-3.0	7.8	2800	4.2	2800	HPTD40080
4.0	10.0	3.0-5.0	7.8	2800	4.2	2800	HPTD40100
4.0	12.0	5.0-7.0	7.8	2800	4.2	2800	HPTD40120
4.8	9.5	1.5-3.5	9.3	5200	4.8	4800	HPTD48095
4.8	12.0	3.5-6.0	9.3	5200	4.8	4800	HPTD48120
4.8	14.5	6.0-8.5	9.3	5200	4.8	4800	HPTD48145
4.8	20.0	7.0-10.0	9.3	5200	4.8	4800	HPTD48200
6.4	10.5	2.8-4.8	14000	13.4	6.4	8500	HPTD64100
6.4	12.5	4.8-6.8	13.4	14000	6.4	8500	HPTD64120
6.4	14.5	6.8-8.8	13.4	14000	6.4	8500	HPTD64140
6.4	16.5	8.8-10.8	13.4	14000	6.4	8500	HPTD64160
6.4	18.5	10.8-12.8	13.4	14000	6.4	8500	HPTD64180
6.4	20.5	11.0-14.5	13.4	14000	6.4	8500	HPTD64200