



# structural rivet superiv - alu/alu - dome head

Reference: SPHD



## Dessin technique

### Description longue (Informations techniques)

Diameter: 4,8  
Diameter: 6,4  
Type: Structural multigrip  
Body / mandrel material: Aluminium-Aluminium  
Head: Dome head  
MAXIMUM CLAMP (mm): 1,6  
maximum assembly range (mm): 15,9  
Maximum tensile: 2000  
Maximum Shear : 2500

### Tableau des caracteristiques

| Diamètre | Longueur | G        | K     | Shear | ØDrill | Tensile | Référence |
|----------|----------|----------|-------|-------|--------|---------|-----------|
| 4.8      | 10.3     | 1.6-6.9  | 10.16 | 2500  | Ø5.0   | 2000    | SPHD48100 |
| 4.8      | 13.5     | 5.4-11.1 | 10.16 | 2500  | Ø5.0   | 2000    | SPHD48140 |

---

|     |      |          |       |      |       |       |            |
|-----|------|----------|-------|------|-------|-------|------------|
| 6.4 | 14.0 | 2.0-9.5  | 13.46 | 5800 | Ø6.8  | 3800  | SPHD64140  |
| 6.4 | 19.0 | 8.9-15.9 | 13.46 | 5800 | Ø6.8  | 3800  | SPHD64200  |
| 9.8 | 21.0 | 3.1-14.5 | 19.00 | 8452 | Ø10.1 | 13122 | SPHD100210 |