



blind rivet nut - stainless steel A2 - cylindrical head

Reference: END



Dessin technique

Description longue (Informations techniques)

Diameter: M5

Diameter: M8

Diameter: M3

Diameter: M4

Diameter: M6

Diameter: M10

Use: Créer un filetage métrique dans le métal

Use: Indoor/Outdoor

Material: Stainless steel

Type: cylindrical threaded

Socket:

Head: Dome head

MAXIMUM CLAMP (mm): 0,3

maximum assembly range (mm): 6

Maximum tensile: 3800

Maximum Shear : 900

Tableau des caracteristiques

Diamètre	Longueur	G	K	Shear	ØDrill	Tensile	Référence
M3	10,9	0.5-3.0	7	900	5.0	3800	END0330
M4	11,0	0.3-3.0	9	2600	6.0	6800	END0430
M4	12,5	3.1-4.0	9	2600	6.0	6800	END0440
M5	13,0	0.3-3.0	10	2900	7.0	11700	END0530
M5	16,0	3.1-4.0	10	2900	7.0	11700	END0540
M6	16,0	0.5-3.0	13	4900	9.0	18000	END0630
M6	17,5	3.1-4.5	13	4900	9.0	18000	END0645
M8	17,5	0.5-3.0	16	6800	11.0	24000	END0830
M8	20,0	3.1-5.5	16	6800	11.0	24000	END0855
M10	19,0	0.5-3.0	19	7800	13.0	29000	END1030
M10	24,0	3.1-6.0	19	7800	13.0	29000	END1060