



blind rivet nut - alu - cylindrical head

Reference: EAD



Dessin technique

Description longue (Informations techniques)

Diameter: M12

Diameter: M4

Diameter: M6

Diameter: M10

Diameter: M3

Diameter: M5

Diameter: M8

Material: Aluminium

Type: cylindrical threaded

Socket:

Head: Dome head

MAXIMUM CLAMP (mm): 0,3

maximum assembly range (mm): 6

Maximum tensile: 2400

Maximum Shear : 800

Tableau des caracteristiques

Diamètre	Longueur	G	K	Shear	ØDrill	Tensile	Référence
M3	10,9	0.5-3.0	7.0	800	5.0	2400	EAD0330
M4	11,0	0.3-3.0	9.0	1000	6.0	2800	EAD0430
M4	12,5	3.1-4.0	9.0	1000	6.0	2800	EAD0440
M5	13,0	0.3-3.0	5.0	1100	7.0	4900	EAD0530
M5	16,0	3.1-4.0	5.0	1100	7.0	4900	EAD0540
M6	16,0	0.5-3.0	13.0	2200	9.0	9200	EAD0630
M6	17,5	3.1-4.5	13.0	2200	9.0	9200	EAD0645
M8	17,5	0.5-3.0	16.0	2400	11.0	14000	EAD0830
M8	20,0	3.1-5.5	16.0	2400	11.0	14000	EAD0855
M10	19,0	0.5-3.0	3800	19.0	13.0	21000	EAD1030
M10	24,0	3.1-6.0	3800	19.0	13.0	21000	EAD1060
M12	25,0	1.0-4.0	4800	23.0	16.0	30000	EAD1240