



# blind rivet nut - alu - countersunk head 90°

Reference: EAK



## Dessin technique

### Description longue (Informations techniques)

Diameter: M10  
Diameter: M5  
Diameter: M8  
Diameter: M4  
Diameter: M6  
Material: Aluminium  
Type: cylindrical threaded  
Head: Countersunk  
MAXIMUM CLAMP (mm): 1,5  
maximum assembly range (mm): 4,5  
Maximum tensile: 2800  
Maximum Shear : 1000

---

# Tableau des caracteristiques

| Diamètre | Longueur | G       | K    | Shear | ØDrill | Tensile | Référence |
|----------|----------|---------|------|-------|--------|---------|-----------|
| M4       | 11,5     | 1.5-3.5 | 9.0  | 1000  | 6.0    | 2800    | EAK0435   |
| M5       | 13,5     | 1.5-4.0 | 5.0  | 1100  | 7.0    | 4900    | EAK0540   |
| M6       | 16,0     | 1.5-4.5 | 12.0 | 2200  | 9.0    | 9200    | EAK0645   |
| M8       | 19,0     | 1.5-4.5 | 14.0 | 2400  | 11.0   | 14000   | EAK0845   |
| M10      | 21,0     | 1.5-4.5 | 15.0 | 3800  | 13.0   | 21000   | EAK1045   |