



bright zinc-plated steel, self-drilling screw,
pan head

Reference: TCC



Dessin technique

Description longue (Informations techniques)

Diameter: 5,5

Diameter: 3,9-4,0

Diameter: 3,5

Diameter: 4,8-5,0

Diameter: 6,3-6,0

Diameter: 2,9

Diameter: 4,2-4,5

Family: Vis métal

K:

Material: white zinc plated steel

Socket:

Head: Cylindrical

MAXIMUM ASSEMBLY CAPACITY (mm): 61

MINIMUM DRILL CAPACITY FOR STEEL (mm): 1,8

Socket type: PHILLIPS (PH-PZ)

MAXIMUM DRILL CAPACITY FOR STEEL (mm): 6
MINIMUM ASSEMBLY CAPACITY(mm): 1,8

Tableau des caracteristiques

Diamètre	Longueur	G	Shear	Tensile	Drill capacity for steel	wrench	maximum speed	Socket	Référence
2.9	13	8	2420	3000	1.8	1800		PH1	TCC29013
2.9	19	14	2420	3000	1.8	1800		PH1	TCC29019
3.5	10	4	2930	5000	2.0	2800		PH2	TCC35010
3.5	13	8	2930	5000	2.0	2800		PH2	TCC35013
3.5	16	8	2930	5000	2.0	2800		PH2	TCC35016
3.5	19	14	2930	5000	2.0	2800		PH2	TCC35019
3.5	22	10	2930	5000	2.0	2800		PH2	TCC35022
3.5	25	20	2930	5000	2.0	2800		PH2	TCC35025
3.5	32	27	2930	5000	2.0	2800		PH2	TCC35032
3.5	38	33	2930	5000	2.0	2800		PH2	TCC35038
3.9	13	7	3650	6000	2.5	3800		PH2	TCC39013
3.9	16	10	3650	6000	2.5	3800		PH2	TCC39016
3.9	19	8	3650	6000	2.5	3800		PH2	TCC39019
3.9	22	16	3650	6000	2.5	3800		PH2	TCC39022
3.9	25	19	3650	6000	2.5	3800		PH2	TCC39025
3.9	32	26	3650	6000	2.5	3800		PH2	TCC39032
3.9	38	32	3650	6000	2.5	3800		PH2	TCC39038
4.2	13	6	4360	7000	3.0	4800		PH2	TCC42013
4.2	16	9	4360	7000	3.0	4800		PH2	TCC42016
4.2	19	12	4360	7000	3.0	4800		PH2	TCC42019
4.2	22	15	4360	7000	3.0	4800		PH2	TCC42022
4.2	25	18	4360	7000	3.0	4800		PH2	TCC42025
4.2	32	25	4360	7000	3.0	4800		PH2	TCC42032
4.2	38	31	4360	7000	3.0	4800		PH2	TCC42038
4.8	13	4	6280	10000	4.0	7000	2000	PH2	TCC48013
4.8	16	7	6280	10000	4.0	7000	2000	PH2	TCC48016
4.8	19	10	6280	10000	4.0	7000	2000	PH2	TCC48019
4.8	22	8	6280	10000	4.0	7000	2000	PH2	TCC48022
4.8	25	16	6280	10000	4.0	7000	2000	PH2	TCC48025
4.8	32	23	6280	10000	4.0	7000	2000	PH2	TCC48032
4.8	38	29	6280	10000	4.0	7000	2000	PH2	TCC48038
4.8	45	36	6280	10000	4.0	7000	2000	PH2	TCC48045
4.8	50	41	6280	10000	4.0	7000	2000	PH2	TCC48050
4.8	60	51	6280	10000	4.0	7000	2000	PH2	TCC48060
4.8	70	61	6280	10000	4.0	7000	2000	PH2	TCC48070
5.5	19	9	8360	12500	5.0	10500	1750	PH3	TCC55019
5.5	25	15	8360	12500	5.0	10500	1750	PH3	TCC55025
5.5	32	22	8360	12500	5.0	10500	1750	PH3	TCC55032
5.5	38	28	8360	12500	5.0	10500	1750	PH3	TCC55038
5.5	50	40	8360	12500	5.0	10500	1750	PH3	TCC55050
6.3	19	8	12270	17000	6.0	17000	1500	PH3	TCC63019
6.3	25	14	12270	17000	6.0	17000	1500	PH3	TCC63025
6.3	32	21	12270	17000	6.0	17000	1500	PH3	TCC63032
6.3	38	27	12270	17000	6.0	17000	1500	PH3	TCC63038
6.3	50	39	12270	17000	6.0	17000	1500	PH3	TCC63050