



bright zinc-plated steel, self-drilling screw,
120° countersunk head

Reference: TFC



Dessin technique

Description longue (Informations techniques)

Diameter: 3,5

Diameter: 4,8-5,0

Diameter: 6,3-6,0

Diameter: 2,9

Diameter: 4,2-4,5

Diameter: 5,5

Diameter: 3,9-4,0

Family: Vis métal

K:

Material: white zinc plated steel

Head: Countersunk

MAXIMUM ASSEMBLY CAPACITY (mm): 66

MINIMUM DRILL CAPACITY FOR STEEL (mm): 1,8

Socket type: PHILLIPS (PH-PZ)

MAXIMUM DRILL CAPACITY FOR STEEL (mm): 6

MINIMUM ASSEMBLY CAPACITY(mm): 4

Tableau des caracteristiques

Diamètre	Longueur	G	Shear	Tensile	Drill capacity for steel	wrench	maximum speed	Socket	Référence
2.9	13	8	2420	3000	1.8	1800		PH1	TFC29013
2.9	16	8	2420	3000	1.8	1800		PH1	TFC29016
2.9	19	14	2420	3000	1.8	1800		PH1	TFC29019
3.5	13	7	2930	5000	2.0	1800		PH2	TFC35013
3.5	16	10	2930	5000	2.0	1800		PH2	TFC35016
3.5	19	8	2930	5000	2.0	1800		PH2	TFC35019
3.5	22	16	2930	5000	2.0	1800		PH2	TFC35022
3.5	25	19	2930	5000	2.0	1800		PH2	TFC35025
3.5	32	26	2930	5000	2.0	1800		PH2	TFC35032
3.9	13	7	3650	6000	2.5	3800		PH2	TFC39013
3.9	16	10	3650	6000	2.5	3800		PH2	TFC39016
3.9	19	8	3650	6000	2.5	3800		PH2	TFC39019
3.9	22	16	3650	6000	2.5	3800		PH2	TFC39022
3.9	25	19	3650	6000	2.5	3800		PH2	TFC39025
3.9	32	26	3650	6000	2.5	3800		PH2	TFC39032
3.9	38	32	3650	6000	2.5	3800		PH2	TFC39038
4.2	13	6	4360	7000	3.0	4800		PH2	TFC42013
4.2	16	9	4360	7000	3.0	4800		PH2	TFC42016
4.2	19	12	4360	7000	3.0	4800		PH2	TFC42019
4.2	22	15	4360	7000	3.0	4800		PH2	TFC42022
4.2	25	18	4360	7000	3.0	4800		PH2	TFC42025
4.2	32	25	4360	7000	3.0	4800		PH2	TFC42032
4.2	38	31	4360	7000	3.0	4800		PH2	TFC42038
4.8	13	4	6280	10000	4.0	7000	2000	PH2	TFC48013
4.8	16	7	6280	10000	4.0	7000	2000	PH2	TFC48016
4.8	19	10	6280	10000	4.0	7000	2000	PH2	TFC48019
4.8	22	8	6280	10000	4.0	7000	2000	PH2	TFC48022
4.8	25	16	6280	10000	4.0	7000	2000	PH2	TFC48025
4.8	32	23	6280	10000	4.0	7000	2000	PH2	TFC48032
4.8	38	29	6280	10000	4.0	7000	2000	PH2	TFC48038
4.8	45	36	6280	10000	4.0	7000	2000	PH2	TFC48045
4.8	50	41	6280	10000	4.0	7000	2000	PH2	TFC48050
4.8	65	56	6280	10000	4.0	7000	2000	PH2	TFC48065
4.8	75	66	6280	10000	4.0	7000	2000	PH2	TFC48075
5.5	19	9	8360	12500	5.0	10500	1750	PH3	TFC55019
5.5	25	15	8360	12500	5.0	10500	1750	PH3	TFC55025
5.5	32	22	8360	12500	5.0	10500	1750	PH3	TFC55032
5.5	38	28	8360	12500	5.0	10500	1750	PH3	TFC55038
5.5	45	35	8360	12500	5.0	10500	1750	PH3	TFC55045
5.5	50	40	8360	12500	5.0	10500	1750	PH3	TFC55050
6.3	25	14	12270	17000	6.0	17000	1500	PH3	TFC63025
6.3	32	21	12270	17000	6.0	17000	1500	PH3	TFC63032
6.3	38	27	12270	17000	6.0	17000	1500	PH3	TFC63038
6.3	50	39	12270	17000	6.0	17000	1500	PH3	TFC63050
6.3	63	52	12270	17000	6.0	17000	1500	PH3	TFC63063