



screw, 120° countersunk head, bright zinc-plated steel

Reference: TFQ



Dessin technique

Description longue (Informations techniques)

Diameter: 4,8-5,0

Diameter: 3,5

Diameter: 3,9-4,0

Diameter: 4,2-4,5

Family: Vis métal

Material: white zinc plated steel

Head: Countersunk

MAXIMUM ASSEMBLY CAPACITY (mm): 71

MINIMUM DRILL CAPACITY FOR STEEL (mm): 2

Socket type: SQUARE (SQ)

MAXIMUM DRILL CAPACITY FOR STEEL (mm): 4

MINIMUM ASSEMBLY CAPACITY(mm): 7

Tableau des caracteristiques

Diamètre	Longueur	G	Shear	Tensile	Drill capacity for steel	wrench	maximum speed	Socket	Référence
3.5	13	7	2930	5000	2.0	2800		SQ1	TFQ35013
3.5	16	10	2930	5000	2.0	2800		SQ1	TFQ35016
3.5	19	8	2930	5000	2.0	2800		SQ1	TFQ35019
3.9	13	7	3650	6000	2.5	3800		SQ2	TFQ39013
3.9	16	10	3650	6000	2.5	3800		SQ2	TFQ39016
3.9	19	8	3650	6000	2.5	3800		SQ2	TFQ39019
3.9	25	19	3650	6000	2.5	3800		SQ2	TFQ39025
3.9	32	26	3650	6000	2.5	3800		SQ2	TFQ39032
3.9	38	32	3650	6000	2.5	3800		SQ2	TFQ39038
4.2	16	9	4360	7000	3.0	4800		SQ2	TFQ42016
4.2	19	12	4360	7000	3.0	4800	2000	SQ2	TFQ42019
4.2	25	18	4360	7000	3.0	4800		SQ2	TFQ42025
4.2	32	25	4360	7000	3.0	4800		SQ2	TFQ42032
4.2	38	31	4360	7000	3.0	4800		SQ2	TFQ42038
4.8	16	7	6280	10000	4.0	7000		SQ2	TFQ48016
4.8	19	10	6280	10000	4.0	7000		SQ2	TFQ48019
4.8	25	16	6280	10000	4.0	7000		SQ2	TFQ48025
4.8	32	23	6280	10000	4.0	7000		SQ2	TFQ48032
4.8	38	29	6280	10000	4.0	7000		SQ2	TFQ48038
4.8	45	36	6280	10000	4.0	7000		SQ2	TFQ48045
4.8	50	41	6280	10000	4.0	7000	2000	SQ2	TFQ48050
4.8	60	51	6280	10000	4.0	7000	2000	SQ2	TFQ48060
4.8	70	61	6280	10000	4.0	7000	2000	SQ2	TFQ48070
4.8	80	71	6280	10000	4.0	7000	2000	SQ2	TFQ48080