



120° countersunk head, bi-métal - A2 stainless steel - hardened steel

Reference: TFXBM



Dessin technique

Description longue (Informations techniques)

Diameter: 4,8-5,0

Diameter: 6,3-6,0

Diameter: 6,0

Diameter: 4,2-4,5

Diameter: 4,0

Diameter: 5,5

Diameter: 3,0

Diameter: 3,5

Family: Vis bois

Material: Stainless steel

Socket: T30

Socket: T20

Head: Countersunk

MAXIMUM ASSEMBLY CAPACITY (mm): 53

MINIMUM DRILL CAPACITY FOR STEEL (mm): 3

Socket type: UNIVERSAL (TS)
MAXIMUM DRILL CAPACITY FOR STEEL (mm): 6
MINIMUM ASSEMBLY CAPACITY(mm): 17

Tableau des caracteristiques

Diamètre	Longueur	G	Drill capacity for steel	wrench	Socket	Référence
4.8	38	10	3.0	5	T20	TFAXBM48038
5.5	45	22	5.0	8	T30	TFAXBM55045
5.5	50	28	5.0	8	T30	TFAXBM55050
6.3	60	38	6.0	12	T30	TFAXBM63060
6.3	75	53	6.0	12	T30	TFAXBM63075