



TCQN self-drilling screw, pan head, A2 stainless steel

Reference: TCQN



Dessin technique

Description longue (Informations techniques)

Diameter: 4,8-5,0

Diameter: 3,5

Diameter: 3,9-4,0

Diameter: 4,2-4,5

Family: Vis menuiserie aluminium

Material: Stainless steel

Head: Cylindrical

MAXIMUM ASSEMBLY CAPACITY (mm): 71

MINIMUM DRILL CAPACITY FOR STEEL (mm): 2

Socket type: SQUARE (SQ)

MAXIMUM DRILL CAPACITY FOR STEEL (mm): 4

MINIMUM ASSEMBLY CAPACITY(mm): 4

Tableau des caracteristiques

Diamètre	Longueur	G	Shear	Tensile	Drill capacity for steel	wrench	maximum speed	Socket	Référence
3.5	10	12	4360	7000	3.0	4800	2000	SQ2	TCQN35010
3.5	13	18	4360	7000	3.0	4800		SQ2	TCQN35013
3.5	16	25	4360	7000	3.0	4800		SQ2	TCQN35016
3.5	19	31	4360	7000	3.0	4800		SQ2	TCQN35019
3.9	13	38	4360	7000	3.0	4800		SQ2	TCQN39013
3.9	16	43	4360	7000	3.0	4800		SQ2	TCQN39016
3.9	19	4	6280	10000	4.0	7000		SQ2	TCQN39019
3.9	25	7	6280	10000	4.0	7000		SQ2	TCQN39025
3.9	32	10	6280	10000	4.0	7000		SQ2	TCQN39032
3.9	38	16	6280	10000	4.0	7000		SQ2	TCQN39038
4.2	13	23	6280	10000	4.0	7000	2000	SQ2	TCQN42013
4.2	16	29	6280	10000	4.0	7000	2000	SQ2	TCQN42016
4.2	19	36	6280	10000	4.0	7000	2000	SQ2	TCQN42019
4.2	25	41	6280	10000	4.0	7000	2000	SQ2	TCQN42025
4.2	32	51	6280	10000	4.0	7000	2000	SQ2	TCQN42032
4.2	38	61	6280	10000	4.0	7000	2000	SQ2	TCQN42038
4.2	50	71	6280	10000	4.0	7000	2000	SQ2	TCQN42050
4.8	13	9	8360	12500	5.0	10500	1750	SQ3	TCQN48013
4.8	16	15	8360	12500	5.0	10500	1750	SQ3	TCQN48016
4.8	19	9	4360	7000	3.0	4800	2000	SQ2	TCQN48019
4.8	22	12	4360	7000	3.0	4800		SQ2	TCQN48022
4.8	25	9.0	4360	7000	3.0	4800		SQ2	TCQN48025
4.8	32	12.0	4360	7000	3.0	4800		SQ2	TCQN48032
4.8	38	7.0	6280	10000	4.0	7000		SQ2	TCQN48038
4.8	45	7	6280	10000	4.0	7000		SQ2	TCQN48045
4.8	50	10	6280	10000	4.0	7000		SQ2	TCQN48050
4.8	60	12	6280	10000	4.0	7000		SQ2	TCQN48060
4.8	70	20	6280	10000	4.0	7000		SQ2	TCQN48070
4.8	80	7	2930	5000	2.0	2800		SQ1	TCQN48080